

DuraMON WS

22", 24" and 27" Wide-Screen



DuraMON WS monitors are Wide-Screen monitors designed for marine and naval mission critical applications.

It values markets demands for:

- Standardisation and easy integration.
- Simplicity in operation.
- Modularity & space saving.
- Long built-state possibility.
- Long up time and less service.
- Low Power consumption.
- Zero Mercury due to LED Backlight

- High quality displays in 22", 24" and 27"
- Full HD 16:9 Wide Screen resolution
- Micro switch keys with membrane
- LED Backlight
- Backlight Dimming from 100% to 0%
- Desk / wall / roof mounting-brackets available.
- Compliant with IEC 60945 and IACS E10.
- DDC communication for day / dusk / night
- Customisation available.

Specifications

DuraMON WS

Display sizes: 22", 22" and 27" Wide Screen LCD (TFT)

Display properties:	Size (Aspect)	Luminance	Contrast	Resolution
	22" (16/9)	250 Cd/m ²	1000:1	1920 x 1080
	22" (16/9)	300 Cd/m ²	1000:1	1920 x 1080
	27" (16/9)	300 Cd/m ²	1200:1	1920 x 1080

View angle: 80° - 89° (L/R/T/B) (typical)

Materials: Front: Sea Water Resistant Aluminium w. black power coating RAL 9005

Rear: Sea Water Resistant Aluminium w. black power coating RAL 9005

Window: Anti Reflection coated front glass

Protection: IP65 front – IP20 rear (IP 22 with optional rear-cover)

DuraMON WS I/O

Video inputs: RGB : Analogue 0.7 Vpp positive at 75Ω,
Separate sync or sync on green
Generally all VESA compatible video modes are supported up to 165MHz (up to UXGA 60Hz and WUXGA 60Hz reduced blanking).
Horizontal sync: 15-100 kHz (automatic)
Vertical sync: 30-85 Hz up to 1280x1024
30-60 Hz up to 1920x1200

DVI: Generally all VESA compatible video modes are supported up to 160MHz (up to UXGA 60Hz and WUXGA 60Hz reduced blanking).
DDC communication for adjustment for Day / Dusk / Night. (Optional extra)

Control inputs: 1x RS232 – for remote control

DuraMON WS Power Supply

Standard: 90-264Vac. 50-60Hz Input

Optional: 18-36Vdc Input

Power Consumption:	Size	P _{TYP} (Watt)	P _{MAX} (Watt)
	22"	20	35
	24"	25	40
	27"	30	45

DuraMON WS Environmental Conditions

Operating Temperature: -15 to 55 °C

Storage Temperature: -25 to 70 °C

Relative Humidity: 8 to 90 %

DuraMON WS Approvals

CE Mark: EN61000-6-2 & EN61000-6-4

Marine: IACS E10 Rev. 5 & IEC 60945 Ed. 4

For marine class approvals – see www.isic-systems.com

DuraMON WS Physical dimensions

Size: 22" 552 (W) x 380 (H) x 68 (D)
24" 601 (W) x 408 (H) x 68 (D)
27" 684 (W) x 452 (H) x 68 (D)

Weight: 22" 9 kg
24" 10kg
27" 11kg

Bracket: Desk / wall / roof bracket and IP22 rear-cover available (optional extra)